

ECO-LINNEA TWIN LED Linear light



Construction:

- 1.2mm Aluminum Body
- Poly carbonate Lens
- Isolated LED driver
- Epistar 2835 LED chips

Electrical control:

- Input voltage range: 100-277V AC
- Frequency: 50-60Hz
- Power factor: >0.95
- Harmonic Distortion: THD<13%



CEILING



SUSPENDED



Kitchen



Classroom



Living room

Model	Wattage	Size	Dimensions(mm)	Voltage	Lumens	LED Quantity	CCT(K)
ECOLED210-NBPC			616X119X40	100-277V	>2100lm/>2600lm	120	CCT 3000 4000 5000 6000 Kelvin
ECOLED220-N BPC-2	40W	2'	616X119X40	100-277V	>4200lm	120	
ECOLED220-NBPC	40W	4'	1226X119X40	100-277V	>4200lm/>5200lm	240	
ECOLED230-NBPC-4	60W	4'	1226X119X40	100-277V	>7200lm	240	
ECOLED225-NBPC	50W	5'	1506X119X40	100-277V	>5250lm/>6500lm	300	
ECOLED230-NBPC	60W	5'	1506X119X40	100-277V	>6300lm/>7800lm	360	
ECOLED240-NBPC	80W	8'	2406X119X40	100-277V	>8400lm/>10400lm	480	
ECOLED260-NBPC	120W	8'	2406X119X40	100-277V	>14400lm	480	